

Rec'd PCT/PTO 03 SEP 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/506655

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 September 2003 (12.09.2003)

PCT

(10) International Publication Number  
WO 03/074796 A1

(51) International Patent Classification: E02D 29/055

(21) International Application Number: PCT/AU03/00274

(22) International Filing Date: 7 March 2003 (07.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PS 0960 7 March 2002 (07.03.2002) AU

(71) Applicant and

(72) Inventor: BLAZEVIC, Paul [AU/AU]; 35 Britannic Crescent, Sovereign Island, Queensland 4216 (AU).

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

(74) Agent: FISHER ADAMS KELLY; Level 13, AMP Place, 10 Eagle Street, Brisbane, Queensland 4000 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF CONSTRUCTION



(57) Abstract: A method of construction includes positioning at least one support member (2) in the ground, forming a foundation (4) substantially adjacent the at least one support member, excavating ground beneath the foundation to a prescribed depth below the surface (5) temporarily forming cavities or voids (8) and supporting bridges (10) beneath the foundations, excavating the supporting bridges and dropping the formed foundation to the prescribed depth. Structures such as walls (12) may be constructed on the foundations prior to dropping the foundations and bracing members (22) may be used to prevent deflection of the walls.

BEST AVAILABLE COPY

WO 03/074796 A1